

LED Reading Light Series

No perfect lamp born with

coincidence
but **design**


Brinno.
LED LIGHTING




Surface mounted

reading light

Brinno
LED LIGHTING



Viogi aluminum by CNC



Horizontal angle 180° adjustable, vertical angle 90° adjustable



Independent reading area



Fast charging with USB or TYPE-C available




Switch:rocker switch on plate



Finished : Matt black, matt white, brushed brass, brushed nickel,



BR-P2205



IP22 | 90° | 180° | SMD | ≥ 90 High CRI


N-20°

Input voltage:AC220-240V
Power: 3W
Lumen : 150Lm ±10%
LED:Osram
CCT:2700K/3000K/4000K
Driver : UL/SAA/TUV/CE listed

Matt Black | Matt White | Brushed Brass | Brushed Nickel



BR-P2205C



IP22 | 90° | 180° | SMD | ≥ 90 High CRI

N-20°

Input voltage:AC220-240V
Power: 3W
Lumen : 150Lm ±10%
LED:Osram
CCT:2700K/3000K/4000K
Driver : UL/SAA/TUV/CE listed
USB Outle : Type-C/ 5V 2.1A fast charger

Matt Black | Matt White | Brushed Brass | Brushed Nickel



Type-C/ 5V 2.1A fast charger

Brinno
LED LIGHTING




Recessed

reading light





BR-P2203



IP22 | 90° | 180° | SMD | CRI ≥ 90

N-20°


Input voltage:AC220-240V
Power: 3W
Lumen : 150Lm ±10%
LED:Osram
CCT:2700K/3000K/4000K
Driver : UL/SAA/TUV/CE listed

Matt Black | Matt White | Brushed Brass | Brushed Nickel



DC24V input

BR-P2204



IP22 | 90° | 180° | SMD | ≥ 90 High CRI


N-20°

Input voltage:DC24V
Power: 3W
Lumen : 130Lm
LED:Osram
CCT:2700K/3000K/4000K
Driver : UL/SAA/TUV/CE listed

Matt Black | Matt White | Brushed Brass | Brushed Nickel

BR-P2203C





IP22 | 90° | 180° | SMD | ≥ 90 High CRI

N-20°

Input voltage:AC220-240V
Power: 3W
Lumen : 130Lm
LED:Osram
CCT:2700K/3000K/4000K
Driver : UL/SAA/TUV/CE listed
Outle : Type-C/ 5V 2.1A fast charger

Matt Black | Matt White | Brushed Brass | Brushed Nickel



Type-C/ 5V 2.1A fast charger




WALL.READING

Brinno.
LED LIGHTING






BR-S2206





S-15° N-24° M-36° M-50°


Input voltage:AC220-240V
Power: 3.5W
Lumen : 250Lm ±10%
LED:Bridgelux
CCT:2700K/3000K/4000K
Driver : UL/SAA/TUV/CE listed



Matt Black Matt White Brushed Brass Brushed Nickel

BR-S2207








S-15° N-24° M-36° M-50°

Input voltage:AC220-240V
Power: 2* 3.5W
Lumen : 2* 250Lm ±10%
LED:Bridgelux
CCT:2700K/3000K/4000K
Driver : UL/SAA/TUV/CE listed








BR-S2208






IP22 | 90° | 180° | SMD | ≥ 90 High CRI

N-20°

Input voltage:AC220-240V
Power: 3W+5W;
LED: Osram;
CCT:2700K/3000K/4000K;
Driver : UL/SAA/TUV/CE listed

Matt Black | Matt White | Brushed Brass | Brushed Nickel






Foshan Brinno Tech Co.,Ltd
www.brinnoled.com | info@brinnoled.com
Add: B2 New Lighting Source Industry Zone, Luocun,Nanhai District, Foshan, Guangdong, China

CEILING LUMINAIRES DOWNLIGHTS

The luminaire within the luminaire



Dual light distribution: Ceiling luminaires outlet their light into the room in two ways. By brilliant optical design,lead the lumen out from the lamp via an integrated focusing/diffusing lens made of crystal glass;at the same times ,light up the surranding area of the downlight on the ceilling via the luminaire glass. The mix of downward directed and vertical luminous intensity ensures excellent visual comfort.









BR-MD084







S-15° N-24° M-36°

Input voltage:AC220-240V
Power: 14W
Lumen : 1400Lm
LED :Bridgelux
CCT:2700K/3000K/4000K
Driver : UL/SAA/TUV/CE listed
Installation: Surface mounted